



Separate Configuration from Code

Configuration in Code

Programmers sometimes "hard code" configuration data in code. Using the example below:

1. What '*configuration data*' is being stored in code?
2. Why is this a bad idea?

```
def connect_to_database():
    """Open a connection to the database.
       Returns: connection to database.
    """
    conn = MySQLdb.connect('pollsdb',
                           user='polls',
                           password='stupid')
    return conn
```

Python has a standard DB-API that supports most databases.

Problems with Configuration in Code

1. Effort to modify when configuration must change
 - and you may make mistakes or miss something
2. Cannot deploy same code in different environments.
 - Example: a "test" server and "production" server
3. Possibly insecure
 - exposes user/password, OAuth credentials, etc.

Where to Put Configuration Data?

1. **In a file.**

Properties file (plain text) or similar
XML or JSON file

2. **In the environment.**

Set environment vars manually or using a script.
Cloud services like Heroku have web form for this.

What About Django?

The Good: All the configuration data is in one file

The Bad: config is still in code. You have to modify it for each different deployment. Must not check it in to Github!

```
import os, sys
SECRET_KEY = 'wjtc3c@k5m!3^0m3dq=e^jff_t%q*blm'

DEBUG = True

ALLOWED_HOSTS = ['*']

INSTALLED_APPS = [
    'polls',
    'django.contrib.admin',
    'django.contrib.auth',
    ...
]
```

Exercise

Look in your own `settings.py` file.

Find at least 4 settings that are either:

- 1) `confidential` - should not be visible to others
- 2) `may need to change` for different deployments, such as running on your own computer vs a server

Exercise

Did you write down at least 4 variables in `settings.py` that should be externalized?

Or are you *too lazy*?

If you didn't do it,
then no point in reading the rest of these slides.

Django Settings

```
# This is confidential so should be externalized
SECRET_KEY = 'wjtc3c@k5m!3^0m3dq=e^jff_t%q*blm'

# Only enable DEBUG for development.
# Should be False when app is deployed.
DEBUG = True

# For development, only allow localhost
ALLOWED_HOSTS = ['*']

# Different database for development and deployed
DATABASES = { ...
    }

# For production, an external server for static
# content is more efficient than Django.
STATIC_URL = '/static/'
```


The 12-Factor App

Heroku recommends 12 characteristics of maintainable web applications.

#3. Store configuration in the environment

3. Store Config in the environment

"Config" is everything that is likely to vary between deployments (staging, production, local dev env.).

database handles: `DATABASE_URL = ...`

credentials for other services your app uses

anything likely to change

OK to use a **configuration file** instead of environment...
if there is a way to specify a different configuration file w/
o changing the code.

Using Environment Variables

Original settings.py:

```
SECRET_KEY = 'wjtc3c@k5m!3^0m3dq=e'
```

1. Create an environment variable for the secret key:

```
# Linux (no space around =)
export SECRET_KEY='wjtc3c@k5m!3^0m3dq=e'
# Windows
set SECRET_KEY = 'wjtc3c@k5m!3^0m3dq=e'
```

2. Modified settings.py using an environment variable:

```
import os
SECRET_KEY = os.getenv('SECRET_KEY')
```

Saving Environment Variables

The value of an environment variable lasts only for the duration of your current terminal or shell session.

To save & restore environment, put the values in a file and "source" the file.

```
# linux or MacOS  
source env.sh
```

Some shells use "." instead of "source": `. env.sh`

This file (env.sh) should be in your project directory and **not committed to git**.

```
export SECRET_KEY='wjtc3c@k5m!3^0m3dq=e'  
export DEBUG=True
```

Better Solutions

Using `os.getenv()` works, but env variables are always interpreted as strings, and you have to remember to "source" the data file before running Django.

There are 2 Python packages that do type conversion for you and automatically look for values in either a file or the environment:

`python-decouple` - flexible, general purpose package

`django-environ` - adds convenience methods for converting strings to types used in `settings.py`

`python-decouple` has better documentation.

Using python-decouple

python-decouple has a 'config' function that imports named values from the environment or a file.

```
# settings.py
from decouple import config

SECRET_KEY = config('SECRET_KEY', default="secret")
DEBUG = config('DEBUG', cast=bool, default=False)
```

`config()` will set 'SECRET_KEY' and 'DEBUG' using either (a) environment variables or (b) values in a file named `.env`. For example:

```
# .env file. values do not need quotes.
SECRET_KEY = wjtc3c@k5m!3^0m3dq=e
DEBUG = False
```

type cast and default values

You can specify a type cast and default value.

The default type is string.

```
DEBUG = config('DEBUG', cast=bool, default=False)
```

Database Connection Info

Before externalization:

```
DATABASES = {  
    'default': {  
        'ENGINE': 'django.db.backends.postgresql',  
        'NAME': 'polls',  
        'USER': 'padmin',  
        'PASSWORD': 'secret',  
        'HOST': 'localhost',  
        'PORT': 5432,  
    }  
}
```


Externalize Database Connection

Using "config" for database parameters is clumsy:

```
DATABASES = {
    'default': {
        'ENGINE': config('DB_ENGINE'),
        'NAME': config('DB_NAME'),
        'USER': config('DB_USER'),
        'PASSWORD': config('DB_PASSWORD'),
        'HOST': config('DB_HOST'),
        'PORT': config('DB_PORT', cast=int),
    }
}
```

```
# File: .env
DB_ENGINE = django.db.backends.postgresql
DB_NAME = polls
DB_USER = padmin
DB_PASSWORD = secret
DB_HOST = 211.compute-1.amazonaws.com
DB_PORT = 5432
```

dj_database_url.parse()

dj_database_url (add-on) can create all the Django database parameters (dict) from a single URL. It is much simpler!

In settings.py use:

```
DATABASES = {
    'default': config('DATABASE_URL',
                     cast=dj_database_url.parse)
}
```

In the .env file or environment you write a single URL:

```
# .env file.
DATABASE_URL=postgres://padmin:secret@localhost:5432/polls
```

Properties File (Java example)

Plain text file containing key-values in the form:

```
key = value
```

You do not need quotes around the value

Commonly used in many programming languages.

```
# Don't commit this file to Git!
jdbc.url =
    jdbc:mysql://cloud.google.com/xxxx
jdbc.user = pollsadmin
jdbc.password = secret
```

Read a Properties File (Java)

Reading a properties file creates a *dictionary* or *map* of keys to values.

In Java:

```
InputStream in = new FileInputStream("myapp.conf");
Properties props = new Properties();
props.load(in);    // read properties from the file
// Get the database url using its key
// in the properties file
String url = props.getProperty("jdbc.url");
System.out.println("The database URL is " + url);
```

Reference

Externalize your Configuration

`https://reflectoring.io/externalize-configuration/`

The 12-Factor App by Heroku, #3 is Configuration.

`https://12factor.net/`